



Shell Rimula R4 X 20W-50

Heavy Duty Diesel Engine Oil

Shell Rimula R4 X is designed to provide Triple Protection to improve engine and oil durability. It helps to lower maintenance and increase reliability of vehicles. It's suitable for most heavy-duty diesel engines for on and off highway applications.



- Triple Protection

Performance, Features & Benefits

• Acid and Corrosion Control

Shell Rimula R4 X shows excellent control of acids by reducing the accumulation of acids and chemical corrosion of engine bearings. Harmful acids from fuel combustion are controlled by using selected detergent additives to neutralise them and help to prevent corrosion of metal surfaces.

• Reduced Engine Wear

Shell Rimula R4 X offers high levels of engine wear protection in the critical areas of the valve train and piston rings and cylinder liners. This wear control is achieved through the addition of anti-wear additives that are designed to form protective films in metal-to-metal contacts when needed under different engine operating conditions and by the use of soot dispersant additives to keep soot particles finely dispersed to help prevent wear.

• Deposit Control

Shell Rimula R4 X helps to prevent oil thickening and the formation of harmful deposits in all areas of the engine, including sludge and piston deposits. The optimised detergent and dispersant additive system for Shell Rimula R4 X keeps engines cleaner than previous-generation Shell Rimula R3 products.

• Severe duty heavy duty diesel engines

Shell Rimula R4 X provides demonstrated protection and performance in the latest high power heavy-duty diesel engines from Europe, US and Japanese manufacturers in both on-highway and off-highway applications.

• High Technology Low Emission Engines

Shell Rimula R4 X is suitable for most modern low emission engines meeting Euro 5, 4, 3, 2, and US 2002 emission requirements.

Shell Rimula R4X is suitable for use with biodiesel per the OEM recommended oil drain intervals

For the latest low emissions engines especially those fitted with exhaust diesel particulate filters (DPF), we recommend the use of our low SAPS products Shell Rimula R4 L, Shell Rimula R5 LE.


Specifications, Approvals & Recommendations

- API CI-4, CH-4
- ACEA E7
- JASO DH-1
- MAN M 3275-1*
- MB-Approval 228.3
- Deutz DQC II-10

* meets the requirements of

For a full listing of equipment approvals and recommendations, please consult your local Shell Technical Helpdesk.

Main Applications



Typical Physical Characteristics

Properties	Method	Shell Rimula R4 X 20W-50
Kinematic Viscosity @40°C mm ² /s	ASTM D445	169.1

Properties			Method	Shell Rimula R4 X 20W-50
Kinematic Viscosity	@100°C	mm ² /s	ASTM D445	18.5
Dynamic Viscosity	@-15°C	mPa s	ASTM D5293	8250
Viscosity Index			ASTM D2270	123
Total Base Number		mgKOH/g	ASTM D2896	10.5
Sulphated Ash		%	ASTM D874	1.45
Density	@15°C	kg/l	ASTM D4052	0.886
Flash Point (COC)		°C	ASTM D92	238
Pour Point		°C	ASTM D97	-33

These characteristics are typical of current production. Whilst future production will conform to Shell's specification, variations in these characteristics may occur.

Health, Safety & Environment

• Health and Safety

Shell Rimula R4 X is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Guidance on Health and Safety is available on the appropriate Safety Data Sheet, which can be obtained from <https://www.epc.shell.com>

• Protect the Environment

Take used oil to an authorised collection point. Do not discharge into drains, soil or water.

Additional Information

• Advice

Advice on applications not covered here may be obtained from your Shell representative.